

IN THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (*Currently Amended*) A nozzle arrangement adapted to be fitted to a ~~pressurised~~ pressurized vessel or container and to permit fluid present in said vessel or container to be dispensed through it under pressure, said nozzle arrangement ~~having~~ comprising:

a body ~~which defines~~ including,

an inlet,

an outlet, and

an internal fluid flow passageway through which fluid can flow from said inlet to said outlet, ~~said body comprising~~,

an actuator means portion ~~which is~~ adapted, upon operation, to engage and open an outlet valve of the ~~pressurised~~ pressurized vessel or container to which the arrangement is attached ~~and thereby to~~ enable fluid present in the ~~pressurised~~ pressurized vessel or container to be released into the nozzle arrangement, and

~~wherein the body of the nozzle arrangement comprises~~

a resiliently deformable wall member ~~which substantially defining defines the entire length or the entire length of the fluid flow passageway, said resiliently deformable wall and being~~ and configured such that,

~~(a) when fluid is caused to flow through the nozzle arrangement in response to the operation of said actuator means, said wall undergoes to~~ undergo a resilient deformation from an initial resiliently-biased configuration, in which ~~said~~ a portion of the passageway is closed, to a distended configuration, ~~whereby in which~~ fluid can flow through said portion of the passageway and be dispensed through the outlet, ~~said wall being further configured when fluid is caused to flow through the nozzle arrangement in response to the operation of said actuator portion, and~~

~~(b) to revert to the initial resiliently-biased configuration when the operation of the actuator means portion has ceased and thereby cause any fluid~~

remaining in the ~~entire length~~ or substantially the entire length of the passageway to be expelled,

wherein the body of the ~~nozzle arrangement being~~ is formed of two interconnected parts, each of said parts having respective abutment surfaces which are contacted together, and

wherein portions of said abutment surfaces from the wall of the body defining said internal fluid flow passageway and at least one of said abutment surfaces of said portions forms said resiliently deformable wall member.

2. (*Currently Amended*) A nozzle arrangement according to claim 1, wherein the outlet is defined, at least in part, by a resiliently deformable wall of the body, which is configured ~~such that,~~

~~when fluid is cause to flow through the nozzle arrangement in response to the operation of said actuator means, said wall undergoes~~ (a) to undergo a resilient deformation from an initial resiliently-biased configuration, in which the outlet is closed, to a distended configuration, ~~whereby in which~~ fluid can flow through said outlet, when fluid is cause to flow through the nozzle arrangement in response to the operation of said actuator portion,

(b) said wall being further configured to revert to the initial resiliently-biased configuration when the operation of the actuator portion ~~means~~ has ceased and thereby cause any fluid remaining in said outlet to be expelled.

3. (*Currently Amended*) A nozzle arrangement according to claim 2, wherein the outlet is an open end of said passageway and the resiliently deformable wall which defines the outlet is the end of the resiliently deformable wall member which defines said portion of the fluid flow passageway.

4. (*Currently Amended*) A nozzle arrangement according to ~~any preceding~~ claim 1, wherein the resilience of the resiliently deformable wall member is uniform along its length.

5. (*Currently Amended*) A nozzle arrangement according to ~~any one of claims claim 1 to 4~~, wherein the resiliently deformable wall member ~~which defines an internal surface of the fluid flow passageway~~ is adapted such that, when the operation of the actuator portion has ceased and the resiliently deformable wall reverts to the initial resiliently-biased configuration, any fluid remaining in the passageway is expelled through the outlet.

6. (*Currently Amended*) A nozzle arrangement according to claim ~~5~~ 1, wherein the resilience of said resiliently deformable wall member varies along its length.

7. (*Currently Amended*) A nozzle arrangement according to ~~claims claim 5 or 6~~, wherein the resilience ~~or elasticity~~ of the resiliently deformable wall member is greater at locations disposed away from the outlet than at locations proximate to said outlet so that, when operation of the actuator portion has ceased, the internal surface fluid flow passageway resiliently deformable wall elastically recoils to ~~the~~ a collapsed configuration ~~preferentially~~ at positions further way from the outlet so as to cause any fluid remaining in said portion of the internal passageway to flow towards, and ~~by~~ be expelled through, the outlet.

8. (*Currently Amended*) A nozzle arrangement according to claim [8] 7, wherein in the resiliently deformable wall defines an internal surface which extends for all, or substantially all, of the length of the fluid flow passageway, and the resilience of the resiliently deformable wall is greater at the inlet end of the passageway than at positions proximate to said outlet, so that, when the operation of the actuator is ceased, the resiliently deformable wall reverts to the initial resiliently-biased configuration preferentially at the inlet so as to cause any fluid remaining on said passageway to flow towards, and be expelled through, the outlet.

9. (*Currently Amended*) A nozzle arrangement according to claim 1 ~~claims 7 or 8~~, wherein the resilience ~~or elasticity~~ of said resilient deformable wall member increases proportionally with increasing distance from the outlet.

10. (*Currently Amended*) A nozzle arrangement according to ~~any preceding~~ claim 1, wherein two or more walls of the body define the internal fluid flow passageway, at least one of which is resiliently deformable and, in the initial resiliently-biased configuration, is resiliently biased against the opposing walls to define a closed passageway.

11. (*Original*) A nozzle arrangement according to claim 10, wherein the internal fluid flow passageway is defined by two walls of the body, at least one said walls being resiliently deformable and providing an internal surface of the passageway which is resiliently biased against the surface formed by the opposing wall in the initial resiliently-biased configuration so as to define a closed passageway.

12. (*Original*) A nozzle arrangement according to claim 1, wherein only one of said walls is resiliently deformable and is resiliently biased to abut the opposing wall in the resiliently biased configuration.

13. (*Currently Amended*) A nozzle arrangement according to claim 1, wherein a first of said abutment surfaces comprises a groove formed in its abutment surface, which extends from an inlet defined by the body to an edge of the abutment surface, said groove forming a first wall of the fluid flow passageway and being adapted to receive a corresponding resiliently deformable ridge member formed on the abutment surface of the second of abutment surfaces, said ridge member being resiliently biased against the surface of said groove when the two abutment surfaces are contacted together to form said initial resiliently biased configuration, said groove being further configured to deform away from said groove to a distended configuration whereby an open passageway is defined when the ~~actuation means~~ actuator portion is operated and fluid is cased to flow through the arrangement under pressure.

14. (*Currently Amended*) A nozzle arrangement according to claim 1, wherein the a terminus of fluid flow passageway at the an edge of said abutment surfaces defines the outlet.

15. (*Currently Amended*) A nozzle arrangement according to ~~any one of claims~~ claim 1 to 15, wherein said two interconnected parts are releasably connected together.

16. (*Currently Amended*) A nozzle arrangement according to ~~any one of claims~~ claim 1 to 15, wherein said two interconnected parts are permanently connected together.

17. (*Currently Amended*) A nozzle arrangement according to ~~any one of claims~~ claim 1 to 17, wherein said two interconnected parts are made from the same material.

18. (*Currently Amended*) A nozzle arrangement according to claim 17, wherein said two interconnected parts are made from a rigid/flexible plastic material.

19. (*Currently Amended*) A nozzle arrangement according to ~~any one of claims~~ claim 1 to 16, wherein one of said two interconnected parts is made from a rigid plastics material and the other of said parts is made from a resiliently deformable material.

20. (*Currently Amended*) A nozzle arrangement according to ~~any one of claims~~ claim 1 to 19, wherein a sealing means is disposed between said abutment surfaces to prevent any fluid that leaks from said internal fluid flow passageway from seeping out of the nozzle arrangement between the two opposing abutment surfaces.

21. (*Currently Amended*) A nozzle arrangement according ~~any one of the preceding claims~~ claim 1, wherein a sealing means is disposed in said fluid flow passageway to provide a substantially airtight seal.

22. (*Original*) A nozzle arrangement according to claim 21, wherein said seal comprises a groove on said resiliently deformable wall and extending across the width of the internal fluid flow passageway, said groove being adapted to receive, and form a sealing engagement with, a ridge member formed on an opposing wall when said resiliently deformable wall is in its initial resiliently biased configuration.

23. (*Currently Amended*) A nozzle arrangement according to claim 21, wherein said seal comprises a ridge member disposed on said resiliently deformable wall and extending across the width of the internal fluid flow passageway, said ridge member being adapted to be received with, and form a sealing engagement with, a ~~groove~~ groove member formed on an opposing wall when said resiliently deformable wall is in its initial resiliently biased configuration.

24. (*Currently Amended*) A nozzle arrangement according to ~~any one of claims~~ claim 21 to 23, wherein said seal is disposed proximate to said outlet.

25. (*Currently Amended*) A nozzle arrangement according to ~~any preceding~~ claim 1, wherein the nozzle arrangement is configured such that the inlet through which fluid accesses the fluid flow passageway during use is disposed directly adjacent to the outlet ~~valve~~ of the pressurized fluid filled vessel or container to which it is adapted to be attached so that fluid dispensed through the outlet ~~valve~~ flows a minimal distance before entering the fluid flow passageway.

26. (*Currently Amended*) A ~~pressurised~~ pressurized fluid-filled vessel or container comprising an outlet valve and a nozzle arrangement as defined in ~~any one of~~ claims claim 1 to 25 fitted thereto such that fluid ejected through said outlet ~~valve~~ during use is caused to flow through said nozzle arrangement.